

## OFFICE OF THE PRINCIPAL, CHRIST COLLEGE, CUTTACK – 753008 QUOTATION CALL NOTICE No. CC/ 743 /2025, Date: 0 8/04 2025



Sealed quotations are invited from registered firms or authorized dealers having (a) O.E.M. Authorization (Original Equipment Manufacturer), (b) Valid Aadhar Udyog Registration, (c) Office as well as Service-Center in the State of Odisha, (d) valid GST, (e) PAN and Income Tax Clearance for procurement of Desktop Computers, Multifunctional Printers, UPS, LED TV, Wireless Mic and Camera for Virtual meeting along with furnishing the copy of above documents. The quotations should reach the undersigned on or before 28<sup>th</sup> April'2025 by 5.00 P.M. through registered post or Speed Post. The authority reserves the right to reject or cancel any or all quotations without assigning any reason thereof. If the last date will be a holiday, then the next working day will be the last date. The dealers should write the name of the materials for which rate is quoted on the top of the envelope.

For details Specifications please visit our College officials website: (www.christcollege.ac.in).

Principal Principal Christ College, Cuttack

F		
1	120	
-	When-	
Č,	25	

0

Desktop Specification

Items	Specification	
	Tower/Micro Tower (15.1 to 26 Litres)	
abinet Form Factor	Intel H670/Intel <sup>®</sup> H770 or higher Chipset	
hipset Number	Intel	
rocessor Make	x86 64-bit architecture	
rocessor	13 Or higher	
rocessor Generation	Intel Core i3 or higher (i5 or i7)	
Processor Description	tatal Corp is 13100 or higher	
Processor Number	Max Turbo Frequency 4.5Ghz, Minimum 4 Cores and 8	
Number of Cores and Threads per Processor	Threads or higher	
Operating System	Windows 11 Home Factory Preloaded	
RAM Size (GB)	DDR-4 8GB 3200 (16 X1) or higher (2 DIIM Slots)	
RAM Expandability up to (using spare DIMM Slots in GB)	64 GB or higher	
	Intel UHD Graphics 770 or higher	
Integrated Graphics Supported for discrete NVIDIA/AMD Graphics Card up to	Yes	
6GB Type of Drives used to populate the Internal Bays	NVMe SSD	
Total HDD Capacity (GB)	NA	
Total SSD Capacity (GB)	512GB NVMe SSD	
Contract of the second s	Optional	
Optical Drive	Two 3.5" (2.5") HDD	
Drive Bays	1 PCI Express 4.0 x16,	
	1 PCI Express 3.0 x1,	
Slots for Upgradation	1 PCI (Full Height),	
44 DAM \$4 D T T T T T T T T T T T T T T T T T T	2 M.2 slots for WLAN & SSD	
	LAN: Integrated 10/100/1000M Front: 1 headphone/microphone combo; 3 Super Speed USB	
Ports and Connectors	Front: 1 headphone/microphone comoo, 5 or parts 5Gbps signalling rate; 2 SuperSpeed USB 10 Gbps signalling rate; 1 USB Type-C, total 6nos USB in front for easy access Rear: 1 HDMI; 1 Serial Port; 1 line in; 1 line out; 1 power connector; 1 RJ-45; 1 DP; 2 USB 2.0	
Firmware Trusted Platform Module	TPM 2.0	
	Security lock slot	
Hardware Security lock slot	180-260Watt Internal power supply with minimum 90%	
Power Supply	efficiency	
POwer Suppry	Bidder should submit OEM bid specific authorization & the same authorization may be verified by the respective OEM if required.	
	OEM must have the ISO 9001,14001, ISO 20001, ISO 27001 Certificate	
Certification	Microsoft Windows, Energy star 8.0 certified	
Certification	Bidder should submit BIS, BEE, EPEAT, UL, RoHS Certificate of	
	products at the time of participation of the Bid.	
(1,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2,2	USB Keyboard; USB Optical Mouse	
Keyboard Mouse	19.5" LED Display with CTO Certified and same must be	
Monitor	belongs to the same OEM	
Years of Warranty	3 Year Onsite Warranty	



600 VA Line Interactive UPS Specifications			
SI. No.	Feature	General Specifications	
1	UPS Capacity (total)	600VA/360W	
2	Input Voltage	230 VAC nominal	
3	Input Frequency	45 - 65 Hz	
4	Brownout Transfer	145 VAC typical	
5	Over-voltage Transfer	290 VAC typical	
6	Voltage on Battery	230 VAC typical (stepped approximated sine wave)	
7	Frequency – On Battery	SOHz typical	
8	Transfer Time	@50 Hz 6 ms typical, 10 ms max	
9	Air Ventilation	Should have Side and Back Honey bee Perforation for heat dispersion	
10	Protection from Humidity & Dust	UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity	
11	Battery Saver Option	UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years	
12	No Load Shutdown	UPS Should work on loads of 2-3 watts also	
13	AC Surge Protection	Full time, 160 joules	
14	Automatic Re start of UPS	In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference	
15	Type (maintenance-free)	12V, 7.2 Ah	
16	Typical recharge time	4-6 hours	
17	Operating Temperature	0° C to 40° C	
18	Storage Temperature	-15°C to 45°C	
19	3 power outlets	With battery backup and surge protection	
20	Power Cord	1.2 meters	
21	Runtime for Single PC load (60W ± 15W)	27 min (normal mode)	
22	Runtime for Workstation PC (100W ±15W)	13 min (normal mode)	
23	Battery Saver (to save on battery life)	Thru toggle button on front panel	
24	Certification	BIS	
25	Designed and Manufactured in India	Yes	
26	Warranty	Zyeasrs	

P-28

PRINTER

	Generic
	Multifunction Machine Printer with Minimum 1 Year On Site
Description of Stores	Warranty, including Cartridge and Power Cord/Adapter
	warranty, including Carnoge and i ottor octavitation
Core Function	Print, Scan and Copy
Print Technology	Laser
Cartridge Technology	Composite Cartridge
Type of Printing	Monochrome (Black)
RAM Size (MB)	256
Storage Capacity (in GB)	0
Storage Capacity (in CD)	
Features	Fax
Operating System Compatibility	Windows 10 and Above,Linux,Mac OS,Windows Server
	Printing
Print Paper Size	A4 and Legal
Minimum Print Speed per	26 to 30
Minute as per ISO/IEC 24734 in	
A4 Size-Monochrome (Black)	
(in PPM)	
(	
Minimum Print Speed per	Not Applicable
Minute as per ISO/IEC 24734 in	
A4 Size-Colour (in PPM)	
Minimum Speed per Minute as	Not Applicable
per ISO/IEC 24734 in A3 Size-	
Mono (in PPM)	
Minimum Speed per Minute as	Not Applicable
per ISO/IEC 24734 in A3 Size-	
Color (in PPM)	
Auto Duplexing Printing/Coping	Yes
(2-sided Feature)	
	Scanning
Maximum Scan Area	A4 and Legal
(Platen/Flatbed Size)	44.45.20
A4 Scan Speed -Colour (Image	11 to 20
Per Minute) @ 300 x 300 dpi	
Scan To Functions	Email
A4 Scan Speed - Mono (Image	11 to 20
Per Minute) @ 300 x 300 dpi	
Fer Minute) @ 500 x 500 apr	
	COPYING
Reduction and Enlargement	Yes
Feature	

P-27

PAPER HANDLING		
Original Document Feeder Type (For Scanning and Copying)	Automatic Document Feeders (ADF)	
Feeder Capacity (Number of Sheets) (For Scanning and Copying)	31 to 40	
Number of Main Paper Tray	1	
Total Paper Tray Combined Capacity (Number) at 75 GSM	101 to 200	
Bypass Tray Facility	No	
If Yes, Bypass Tray Capacity	0 .	
Connectivity		
Connectivity	USB Port,Ethernet Port,Wi-Fi	
Accessories Provided	USB Cable	
Minimum Yield of the Cartridge/Ink/Toner supplied with Machine as per IS/ISO/IEC: 19752/2017 for Black (Number of Prints) Minimum Yield of the Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints)	Performance 700 0	
Minimum Duty Cycle (Number of Prints/Month)	10,001 to 20,000	
	POWER	
Power Supply	Single Phase AC 220 - 240 V, 50 - 60 Hz	
Maximum Power Consumption (in Watt)	1300	
Environmental		
Minimum Operating Temperature (Degree C)	10	
Maximum Operating Temperature (Degree C)	30	

E

8-2b

P-25

Minimum Operating Humidity (%RH)	20
Maximum Operating Humidity (%RH)	. 08
	Dimension
Standard Machine Weight with	11
Single Tray (in Kg)	
	Certification
BIS CRS Compliance	Yes as per IS 13252 (Part 1)
Maximum Number of Prints	30000
covered under Product warranty	
(Whichever is earlier)	
EPR Registration in respect of	Yes
the manufacturer/authorised	
importer as per E waste rules	
as amended up to date	
Agreed to Provide a copy of	Yes
EPR Registration Certificate to	
the Buyer on Demand	
2. ·	
1	

LED TV

0

## p-24

		All of the Art Art and
	Screen Size	65
	Brightness (cd/m²)	350Nits or better
General Features	Contrast Ratio	1200:1
	Dynamic Contrast Ratio	400,000:1
	Response Time (ms)	8.0
	Display resolution (H x V, pixels)	3840 x 2160
	HDR (High Dynamic Range) compatiblity	Yes (HDR10, HLG)
	Aspect Ratio	16:9
	Portrait/Tilt Compatibility	Yes
	Dimming type	Frame Dimming
	Display Device	LCD
	Panel Type	IPS
	Backlight type	Direct LED
Display features	Color gamut (NTSC)	69%
Display learnies	Operation time	16/7
	Haze (%)	1%
	Viewing Angle (Right/Left)	178 (89/89) degree
		178 (89/89) degree
	Viewing Angle (Up/Down)	
	HDMI Signal	4096 x 2160p (24, 50, 60 Hz) 3840 x 2160p (24, 25, 30, 50 60 Hz), 1080p (30, 50, 60 Hz) 1080/24p, 1080i (50, 60 Hz) 720p (30, 50, 60 Hz), 720/24p, 576p, 576i 480p,480i
	Speaker Position	Down Firing
Audio Specs	Audio Power Output	10W + 10W
	Pro settings	Yes (Simple Pro settings men
Professional	HDMI auto wake-up	Yes
features	Operating System	Android TV
	On-board Storage (GB)	16GB
	RAM	3GB
	Wi-Fi Certified	Yes
Network Specs	Wireless LAN	Integrated
	USB playback codecs	MPEG1:MPEG1/MPEG2 PS:MPEG2/MPEG2 WEBM:AV1/AC4/ogg/AAC
Convenience features	On Screen Clock	Yes
	Sleep Timer	Yes
	On/Off Timer	Yes
	Chromecast built-in	Yes
	Apple AirPlay	Yes
	IP Control	Yes
Control Specs	RS-232C Control	Yes
Control specs	HDMI-CEC	Yes
	HDCP	HDCP2.3 (for HDMI1/2/3)
	Composite Video Input (s)	1 (Side, Mini jack)

	HDMI inputs total	3 (3Side)
Inputs and outputs	Analog Audio Input (s) (Total)	1 (Side Analog Conversion)
	Digital Audio Output (s)	1 (Side)
	USB ports	2 (Side)
	Ethernet inputs	1 (Side)
Design features	VESA <sup>®</sup> Hole Pitch (W x H)	300 x 300 mm
Environment Specs	Rated Power Consumption	226W
	Power Consumption (in Standby)	0.5 W
	Dynamic Backlight Control	Yes
	Power Saving Mode / Back Light Off Mode	Yes
Measurements Weight	Dimension of TV without Stand (W x H x D)	1462 x 842 x 71 mm
	Dimension of TV with Stand (W x H x D)	1462 x 912 x 338 mm
	Dimension of Package Carton (W x H x D)	1588 x 965 x 184 mm
	Weight of TV without Stand	20.4 kg
	Weight of TV with Stand	21.3 kg
	Weight of Package Carton (Gross)	28 kg

Ľ

f.

Buy Logitech Master Series Graphite MX Brio 4K Ultra Hd Web Camera, 960-001548 Online at Best Prices - Industrybuying //25, 11:48 AM O Offers GST Renelits Recome o Seller Bull Order, HADS (2) There order Care mindustry buying com 8849449053 F. P.-22 Shop By Cotingory 88 Industrybuying Q CAMERA. Category to and e Login WEB #24,779 (Inc) of all laxes) share < Home / IT Security / Computer Accessories / WEBCAM / Logitech Master Series Oraphite M 20.999 · 18% 017 O BUR DISCOUNT The Ships within \$ days Logitech Master Series Graphite MX Brio 4K NOT PERSONS OBEN. OFF Ultra Hd Web Camera, 960-001548 Lanmur t: Plants bilans () Visit the Logitech Store 1 Order Quantity - I EMI starts at #2202/month No Cost EMI available EMI options Bulk quantity Discounts!! View Offers AVAILABLE OFFERS Diecourted price per Get up to \$4,000° on a min. order value of \$5,499 select Quantity Sirst-time BET users only. TEC opply plece (incl of all YDDE (man) Get up to \$3,500° on a min order value of \$5,452 0 First-ome 828 users only 16C opply 123.980 14 0 2-3 YNER \$23,740 53 4-5 0 273,500 93 FEATURES More Details 0 6-7 173,341 19 n 8-1700/8 Country of Origin Switzerland USB-C to USB-C ADD TO CART BUYNOW Connectivity Advanced Autolocus Focus Type ٢ 8 ۲/ MX Brio, Mount Clip MX Bro, Mount Clip with Removable Adapter, USB-C to C 3.0 Cable, User Documentation 0.0 Connect with a Product taperi Customized Price Package Contains Calibook O Check Delivery Details More Logitech WEBCAM products More WIBCAM products Entre Franciste Check PREPAID AVONODIA EA PARTCOD Unavailable 100% Original 100% Buyer Worranty as per Secure TOP COD Available payments protection Brands brand Products Avointia ສ**ອ**ໃນເກ OF TURN period 7 SPECIFICATIONS DESCRIPTION days Country of Origin switzeriand Connectivity USB-C to USB-C Cable UN. Focus Type Advanced Autofocus MX Brio, Mount Clip with Removable Adapter. USB-C to C 3 0 Cable, User Documentation Package Contains Microphone Type Dual Beamformina Colles NEED-NE PHONE ROLD FLACTMAR Land and the second a Width 98 mm - 前 主点的后点完了 4x Digital Zoom Zoom Web Camero Type of Product Port No MODELO-4KORPT 44 mm Height Weight 137 g Lens Type Gloss U\$8 3.0 interioce Graphite Color Resolution 4K/30 tps, 1060p/60 tps 8.5 MP Sony STARVIS Image Sensor

960-001548

Model No